

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTR 3-26/26 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton |
Best Efficiency Point 14 GPM @
670 FTH | Motor 3/60/208-230-460
Volt, 5 HP | Pump Depth 23.30" |
Nema Version



SKU: 96515429

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTR 3-26/26 A-
WB-A-HUUV

Part Number 96515429

PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate

www.pfcstore.com - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

Estimated Delivery is 3 to 4 weeks

[MTR Specs](#)

[MTR Manual](#)

ADDITIONAL INFORMATION

Weight	140 lbs
Dimensions	56 × 18 × 18 in
Best Efficiency Point	14 GPM @ 670 FTH
Connections	1.25" NPT
Horse Power	5
Length	Pump Depth 23.30"
Phase	3
Voltage	208-230-460
Wetted Material	CAST IRON-304SS-VITON