

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS MTR 3-5/5 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton |  
Best Efficiency Point 14 GPM @  
117 FTH | Motor 3/60/208-230-460  
Volt, 1 HP | Pump Depth 8.43" |  
Nema Version



---

**SKU:** 96515402

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTR 3-5/5 A-WB-  
A-HUUV

**Part Number** 96515402

## PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

**Estimated Delivery is 3 to 4 weeks**

[MTR Specs](#)

[MTR Manual](#)

## ADDITIONAL INFORMATION

|                              |                                       |
|------------------------------|---------------------------------------|
| <b>Weight</b>                | 50 lbs                                |
| <b>Dimensions</b>            | 50 × 18 × 18 in                       |
| <b>Best Efficiency Point</b> | <a href="#">14 GPM @ 117 FTH</a>      |
| <b>Connections</b>           | <a href="#">1.25" NPT</a>             |
| <b>Horse Power</b>           | <a href="#">1</a>                     |
| <b>Length</b>                | <a href="#">Pump Depth 8-7/16"</a>    |
| <b>Phase</b>                 | <a href="#">3</a>                     |
| <b>Voltage</b>               | <a href="#">208-230-460</a>           |
| <b>Wetted Material</b>       | <a href="#">CAST IRON-304SS-VITON</a> |

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

Material: Cast Iron-304SS-Viton | Best Efficiency Point 14 GPM @ 117 FTH |  
Motor 3/60/208-230-460 Volt, 1 HP | Pump Depth 8.43" | Nema Version