PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTR 5-24/24 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton |
Best Efficiency Point 25 GPM @
660 FTH | Motor 3/60/208-230-460
Volt, 7.5 HP | Pump Depth 30" |
Nema Version



SKU: 96515445

Stock: Out of stock contact us for

lead time

Categories: <u>Grundfos</u> <u>Coolant/Condensate Pumps</u>

Model Number MTR 5-24/24 A-WB-A-HUUV Part Number 96515445

PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate



www.pfcestore.com - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

Estimated Delivery is 3 to 4 weeks

MTR Specs

MTR Manual

ADDITIONAL INFORMATION

Weight 150 lbs

Dimensions $55 \times 18 \times 18$ in

Best Efficiency Point 25 GPM @ 660 FTH

Connections 1.25" NPT

Horse Power 7.5

Length Pump Depth 30"

Phase 3

Voltage <u>208-230-460</u>

Wetted Material CAST IRON-304SS-VITON