



GRUNDFOS MTRE 1-22/22 COOLANT PUMP THREE PHASE, 200-240 VOLTS- NEMA VERSION

Best Efficiency Point 5 GPM @ 785
FTH | Pump Depth 20.50"



SKU: 99528824

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTRE 1-22/22 A-
WB-A-HUUV

Part Number 99528824

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
 - Mechanical shaft seal according to EN 12756.
 - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

ADDITIONAL INFORMATION

Weight	95 lbs
Dimensions	48 × 14 × 14 in
Best Efficiency Point	5 GPM @ 785 FTH
Connections	1.25" NPT
Horse Power	3
Length	Pump Depth 20.50"
Phase	3
Voltage	200-240
Wetted Material	CAST IRON-304SS-VITON

www.pfcstore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point 5 GPM @ 785 FTH | Pump Depth 20.50"