

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTRE 10-8/8 COOLANT PUMP 3 PHASE, 200-240 VOLTS-NEMA VERSION

Best Efficiency Point 45 GPM @ 350 FTH | Pump Depth 12.90"



SKU: 99528834 Stock: Out of stock contact us for lead time Categories: <u>Grundfos</u> <u>Coolant/Condensate Pumps</u>

Model Number MTRE 10-8/8 A-WB-A-HUUV Part Number 99528834

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

• Dimensions according to DIN 5440.

PFC eStore

September 6, 2025



www.pfcestore.com - 763-425-7890 / 800-328-2350

• Impellers, intermediate chambers and spline shaft are made of Stainless steel.

• Mechanical shaft seal according to EN 12756.

• Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanentmagnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

MTRE Specs

MTRE Manual

ADDITIONAL INFORMATION

| Weight | 210 lbs |
|------------------------------|-------------------------|
| Dimensions | 42 × 16 × 16 in |
| Best Efficiency Point | <u>45 GPM @ 345 FTH</u> |
| Connections | <u>2" NPT</u> |
| Horse Power | <u>7.5</u> |
| Length | Pump Depth 12.80" |
| Phase | <u>3</u> |
| Voltage | 200-240 |
| Wetted Material | CAST IRON-304SS-VITON |