



GRUNDFOS MTRE 15-2/1 COOLANT PUMP THREE PHASE, 200-240 VOLTS- NEMA VERSION

Best Efficiency Point 80 GPM @ 50
FTH | Pump Depth 7.01"



SKU: 99528837

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTRE 15-2/1 A-
WB-A-HUUV

Part Number 99528837

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
 - Mechanical shaft seal according to EN 12756.
 - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

ADDITIONAL INFORMATION

Weight	90 lbs
Dimensions	32 × 16 × 16 in
Best Efficiency Point	80 GPM @ 50 FTH
Connections	2" NPT
Horse Power	2
Length	Pump Depth 7-1/16"
Phase	3
Voltage	200-240
Wetted Material	CAST IRON-304SS-VITON

www.pfcstore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point 80 GPM @ 50 FTH | Pump Depth 7.01"