



GRUNDFOS MTRE 1S-13/13 COOLANT PUMP THREE PHASE, 440-480 VOLTS- NEMA VERSION

Best Efficiency Point 4 GPM @ 330
FTH | Pump Depth 14.10"



SKU: 98400099

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTRE 1S-13/13 A-
WB-A-HUUV

Part Number 98400099

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron - all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

www.pfcestore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
 - Mechanical shaft seal according to EN 12756.
 - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

ADDITIONAL INFORMATION

| | |
|------------------------------|---------------------------------------|
| Weight | 80 lbs |
| Dimensions | 36 × 14 × 14 in |
| Best Efficiency Point | 4 GPM @ 330 FTH |
| Connections | 1.25" NPT |
| Horse Power | 1 |
| Length | Pump Depth 14-1/8" |
| Phase | 3 |
| Voltage | 440-480 |
| Wetted Material | CAST IRON-304SS-VITON |

www.pfcestore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point 4 GPM @ 330 FTH | Pump Depth 14.10"