



## GRUNDFOS MTRE 1S-21/21 COOLANT PUMP SINGLE PHASE, 200-240 VOLTS- NEMA VERSION

Best Efficiency Point 4 GPM @ 450  
FTH | Pump Depth 19.80"



**SKU:** 98400094

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTRE 1S-21/21 A-  
WB-A-HUUV

**Part Number** 98400094

## PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
  - Mechanical shaft seal according to EN 12756.
  - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

## Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

## ADDITIONAL INFORMATION

|                              |                                       |
|------------------------------|---------------------------------------|
| <b>Weight</b>                | 90 lbs                                |
| <b>Dimensions</b>            | 40 × 14 × 14 in                       |
| <b>Best Efficiency Point</b> | <a href="#">4 GPM @ 450 FTH</a>       |
| <b>Connections</b>           | <a href="#">1.25" NPT</a>             |
| <b>Horse Power</b>           | <a href="#">1.5</a>                   |
| <b>Length</b>                | <a href="#">Pump Depth 19.80"</a>     |
| <b>Phase</b>                 | <a href="#">1</a>                     |
| <b>Voltage</b>               | <a href="#">200-240</a>               |
| <b>Wetted Material</b>       | <a href="#">CAST IRON-304SS-VITON</a> |

**www.pfcstore.com - 763-425-7890 / 800-328-2350**

Best Efficiency Point 4 GPM @ 450 FTH | Pump Depth 19.80"