



GRUNDFOS MTRE 32-3/3 COOLANT PUMP THREE PHASE, 440-480 VOLTS- NEMA VERSION

Best Efficiency Point 100 GPM @
254 FTH | Pump Depth 11.50"



SKU: 99077602

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTRE 32-3/3 A-
WB-A-HUUV

Part Number 99077602

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron - all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
 - Mechanical shaft seal according to EN 12756.
 - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

ADDITIONAL INFORMATION

Weight	292 lbs
Dimensions	48 × 16 × 16 in
Best Efficiency Point	100 GPM @ 260 FTH
Connections	2.50" ANSI FLANGE
Horse Power	15
Length	Pump Depth 11.50"
Phase	3
Voltage	440-480
Wetted Material	CAST IRON-304SS-VITON

www.pfcstore.com - 763-425-7890 / 800-328-2350

Best Efficiency Point 100 GPM @ 254 FTH | Pump Depth 11.50"