

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTRE 32-3/3 COOLANT PUMP THREE PHASE, 440-480 VOLTS-NEMA VERSION

Best Efficiency Point 100 GPM @ 254 FTH | Pump Depth 11.50"



SKU: 99077602 Stock: Out of stock contact us for lead time Categories: <u>Grundfos</u> <u>Coolant/Condensate Pumps</u>

Model Number MTRE 32-3/3 A-WB-A-HUUV Part Number 99077602

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

• Dimensions according to DIN 5440.

PFC eStore Pumps, Filters & Controls store with B2B August 7, 2025



www.pfcestore.com - 763-425-7890 / 800-328-2350

• Impellers, intermediate chambers and spline shaft are made of Stainless steel.

• Mechanical shaft seal according to EN 12756.

• Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanentmagnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

MTRE Specs

MTRE Manual

ADDITIONAL INFORMATION

Weight	292 lbs
Dimensions	48 × 16 × 16 in
Best Efficiency Point	<u>100 GPM @ 260 FTH</u>
Connections	2.50" ANSI FLANGE
Horse Power	<u>15</u>
Length	Pump Depth 11.50"
Phase	<u>3</u>
Voltage	440-480
Wetted Material	CAST IRON-304SS-VITON