PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTRE 32-4/4 COOLANT PUMP THREE PHASE, 440-480 VOLTS-NEMA VERSION

Best Efficiency Point 100 GPM @ 350 FTH | Pump Depth 14.30"



SKU: 98472473

Stock: Out of stock contact us for

lead time

Categories: <u>Grundfos</u> <u>Coolant/Condensate Pumps</u>

Model Number MTRE 32-4/4 A-WB-A-HUUV Part Number 98472473

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

• Dimensions according to DIN 5440.



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
 - Mechanical shaft seal according to EN 12756.
 - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

MTRE Specs

MTRE Manual

ADDITIONAL INFORMATION

Weight 450 lbs

Dimensions $48 \times 16 \times 16$ in

Best Efficiency Point 100 GPM @ 350 FTH

Connections 2.50" ANSI FLANGE

Horse Power <u>20</u>

Length Pump Depth 14.30"

Phase <u>3</u>

Voltage 440-480

Wetted Material CAST IRON-304SS-VITON