

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS MTRE 45-2/1-1 COOLANT PUMP THREE PHASE, 200-240 VOLTS- NEMA VERSION

Best Efficiency Point 150 GPM @  
90 FTH | Pump Depth 9.61"



**SKU:** 99528843

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTRE 45-2/1-1 A-  
WB-A-HUUV

**Part Number** 99528843

## PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
- Mechanical shaft seal according to EN 12756.
- Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

**Estimated Delivery is 3 to 4 weeks**

[MTRE Specs](#)

[MTRE Manual](#)

## ADDITIONAL INFORMATION

|                              |  |
|------------------------------|--|
| <b>Weight</b>                | 280 lbs                                      |
| <b>Dimensions</b>            | 44 × 18 × 18 in                              |
| <b>Best Efficiency Point</b> | <a href="#"><u>150 GPM @ 90 FTH</u></a>      |
| <b>Connections</b>           | <a href="#"><u>3" ANSI FLANGE</u></a>        |
| <b>Horse Power</b>           | <a href="#"><u>7.5</u></a>                   |
| <b>Length</b>                | <a href="#"><u>Pump Depth 9-7/8"</u></a>     |
| <b>Phase</b>                 | <a href="#"><u>3</u></a>                     |
| <b>Voltage</b>               | <a href="#"><u>200-240</u></a>               |
| <b>Wetted Material</b>       | <a href="#"><u>CAST IRON-304SS-VITON</u></a> |