



GRUNDFOS MTRE 5-20/20 COOLANT PUMP THREE PHASE, 200-240 VOLTS- NEMA VERSION

Best Efficiency Point 30 GPM @
620 FTH | Pump Depth 25.80"



SKU: 99528829

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTRE 5-20/20 A-
WB-A-HUUV

Part Number 99528829

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
- Mechanical shaft seal according to EN 12756.
- Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

ADDITIONAL INFORMATION

Weight	197 lbs
Dimensions	54 × 14 × 14 in
Best Efficiency Point	<u>30 GPM @ 610 FTH</u>
Connections	<u>1.25" NPT</u>
Horse Power	<u>7.5</u>
Length	<u>Pump Depth 25.8"</u>
Phase	<u>3</u>
Voltage	<u>200-240</u>
Wetted Material	<u>CAST IRON-304SS-VITON</u>