



## GRUNDFOS MTRE 5-20/20 COOLANT PUMP THREE PHASE, 440-480 VOLTS- NEMA VERSION

Best Efficiency Point 30 GPM @  
620 FTH | Pump Depth 25.80"



**SKU:** 99077566

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTRE 5-20/20 A-  
WB-A-HUUV

**Part Number** 99077566

## PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
  - Mechanical shaft seal according to EN 12756.
  - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

## Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	197 lbs
<b>Dimensions</b>	54 × 14 × 14 in
<b>Best Efficiency Point</b>	<a href="#">30 GPM @ 610 FTH</a>
<b>Connections</b>	<a href="#">1.25" NPT</a>
<b>Horse Power</b>	<a href="#">7.5</a>
<b>Length</b>	<a href="#">Pump Depth 25.8"</a>
<b>Phase</b>	<a href="#">3</a>
<b>Voltage</b>	<a href="#">440-480</a>
<b>Wetted Material</b>	<a href="#">CAST IRON-304SS-VITON</a>

**www.pfcstore.com - 763-425-7890 / 800-328-2350**

Best Efficiency Point 30 GPM @ 620 FTH | Pump Depth 25.80"