PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTRE 5-3/3 COOLANT PUMP SINGLE PHASE, 200-240 VOLTS-NEMA VERSION

Best Efficiency Point 30 GPM @ 70 FTH | Pump Depth 7.72"



SKU: 98400070

Stock: Out of stock contact us for

lead time

Categories: <u>Grundfos</u> <u>Coolant/Condensate Pumps</u>

Model Number MTRE 5-3/3 A-WB-A-HUUV
Part Number 98400070

PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

• Dimensions according to DIN 5440.



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
 - Mechanical shaft seal according to EN 12756.
 - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

Estimated Delivery is 3 to 4 weeks

MTRE Specs

MTRE Manual

ADDITIONAL INFORMATION

Weight 75 lbs

Dimensions $30 \times 14 \times 14$ in

Best Efficiency Point 30 GPM @ 70 FTH

Connections 1.25" NPT

Horse Power $\underline{1}$

Length Pump Depth 7-3/4"

Phase $\underline{1}$

Voltage 200-240

Wetted Material CAST IRON-304SS-VITON