



## GRUNDFOS MTRE 5-8/8 COOLANT PUMP THREE PHASE, 440-480 VOLTS- NEMA VERSION

Best Efficiency Point 30 GPM @  
240 FTH | Pump Depth 13"



**SKU:** 98400084

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTRE 5-8/8 A-WB-  
A-HUUV

**Part Number** 98400084

## PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron - all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
  - Mechanical shaft seal according to EN 12756.
  - Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

## Estimated Delivery is 3 to 4 weeks

[MTRE Specs](#)

[MTRE Manual](#)

## ADDITIONAL INFORMATION

|                              |                                       |
|------------------------------|---------------------------------------|
| <b>Weight</b>                | 115 lbs                               |
| <b>Dimensions</b>            | 40 × 14 × 14 in                       |
| <b>Best Efficiency Point</b> | <a href="#">30 GPM @ 239 FTH</a>      |
| <b>Connections</b>           | <a href="#">1.25" NPT</a>             |
| <b>Horse Power</b>           | <a href="#">3</a>                     |
| <b>Length</b>                | <a href="#">Pump Depth 13"</a>        |
| <b>Phase</b>                 | <a href="#">3</a>                     |
| <b>Voltage</b>               | <a href="#">440-480</a>               |
| <b>Wetted Material</b>       | <a href="#">CAST IRON-304SS-VITON</a> |

**www.pfcestore.com - 763-425-7890 / 800-328-2350**

Best Efficiency Point 30 GPM @ 240 FTH | Pump Depth 13"