

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS MTRE 64-2/2 COOLANT PUMP THREE PHASE, 440-480 VOLTS- NEMA VERSION

Best Efficiency Point 260 GPM @  
240 FTH | Pump Depth 9.80"



**SKU:** 98472484

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTRE 64-2/2 A-  
WB-A-HUUV

**Part Number** 98472484

## PRODUCT DESCRIPTION

MTRE Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel.

The pump has the following characteristics TEST:

- Dimensions according to DIN 5440.

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
- Mechanical shaft seal according to EN 12756.
- Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service.

The pump is fitted with a 1-phase or 3 phase, fan-cooled, permanent-magnet, synchronous motor.

**Estimated Delivery is 3 to 4 weeks**

[MTRE Specs](#)

[MTRE Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	510 lbs
<b>Dimensions</b>	48 × 18 × 18 in
<b>Best Efficiency Point</b>	<a href="#">260 GPM @ 240 FTH</a>
<b>Connections</b>	<a href="#">3" ANSI FLANGE</a>
<b>Horse Power</b>	<a href="#">25</a>
<b>Length</b>	<a href="#">Pump Depth 9.84"</a>
<b>Phase</b>	<a href="#">3</a>
<b>Voltage</b>	<a href="#">440-480</a>
<b>Wetted Material</b>	<a href="#">CAST IRON-304SS-VITON</a>