

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS IMPELLER 15HP 030-070

500 GPM @ 75 FTH Best Efficiency
Point | Ansi Class 125lbs, 4" x 3" |
Lifetime of no shaft alignments |
Wetted Material: Cast Iron-
Stainless-EPDM | 3/60/230-460V,
3600RPM



SKU: 92560300

Stock: Out of stock contact us for
lead time

Categories: [Paco LC & NBS
Pumps](#)

Model Number

030-070/5.04AASG6S2ESBQQENX2

Part Number 92560300

PRODUCT DESCRIPTION

Benefits

- 35 % smaller footprint than frame mount design

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Rapid mechanical seal access without motor removal
 - Lifetime of no alignment
- Footed volute and motor require no base
 - No grouting
- Integrally cast diffuser vane reduces turbulence and need for suction guides


11.1.8 Shaft seals

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants.

Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F (0 °C) are mainly intended for coolants.



We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

| Shaft seal diameter [mm] | | | | | 28, 38 | 48 | 55 | 60 |
|---|-------------------------------|--------|------|------------------------------------|-----------------------------|----------|----------|----------|
| Shaft seal type | Seal faces | Rubber | Code | Temperature range | Max. pressure [PSI] ([bar]) | | | |
|  Bellows seal, type B, unbalanced | AQ ₁ | EPDM | BAQE | 32-248 °F (0-120 °C) | 232 (16) | 232 (16) | 232 (16) | 232 (16) |
| | BQ ₁ | FKM | BBQV | 32-194 °F (0-90 °C) | 232 (16) | 232 (16) | 232 (16) | 232 (16) |
| | Q ₇ Q ₇ | EPDM | BQQE | -13 to +248 °F (-25 to +120 °C) | 232 (16) | 232 (16) | 232 (16) | 232 (16) |
| | Q ₇ Q ₇ | FKM | BQQV | 14 to 194 °F (-10 to +90 °C) | 232 (16) | 232 (16) | 232 (16) | 232 (16) |

Estimated delivery 3 to 4 weeks. Contact us for actual lead time

[Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight 500 lbs

Dimensions 42 × 20 × 22 in

Best Efficiency Point [520 GPM @ 70 FTH](#)

www.pfcestore.com - 763-425-7890 / 800-328-2350