

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS IMPELLER 20HP 015-095

280 GPM @ 170 FTH Best
Efficiency Point | Ansi Class 125lbs,
2.5" x 1.50" | Lifetime of no shaft
alignments | Wetted Material: Cast
Iron-Stainless-EPDM |
3/60/230-460, 3600RPM



SKU: 92560266

Stock: Out of stock contact us for
lead time

Categories: [Paco LC & NBS
Pumps](#)

Model Number

015-095/7.01AASG6S2ESBQQEOX2

Part Number 92560266

PRODUCT DESCRIPTION

Benefits

- 35 % smaller footprint than frame mount design

www.pfcestore.com - 763-425-7890 / 800-328-2350

- Rapid mechanical seal access without motor removal
- Lifetime of no alignment
- Footed volute and motor require no base
- No grouting
- Integrally cast diffuser vane reduces turbulence and need for suction guides

11.1.8 Shaft seals

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants.
Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F (0 °C) are mainly intended for coolants.

We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

Table with 7 columns: Shaft seal diameter [mm], Shaft seal type, Seal faces, Rubber, Code, Temperature range, and Max. pressure [PSI] ([bar]). It lists specifications for Bellows seal, type B, unbalanced across four configurations (AQ1, BQ1, Q7Q7) with EPDM and FKM rubber options.

Estimated delivery 3 to 4 weeks. Contact us for actual lead time
Specs
Manual

ADDITIONAL INFORMATION

Weight 525 lbs
Dimensions 46 x 22 x 22 in
Best Efficiency Point 300 GPM @ 170 FTH

www.pfcestore.com - 763-425-7890 / 800-328-2350