

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS IMPELLER 25HP 030-070

600 GPM @ 115 FTH Best
Efficiency Point | Ansi Class 125lbs,
4" x 3" | Lifetime of no shaft
alignments | Wetted Material: Cast
Iron-Stainless-EPDM |
3/60/230-460V, 3600RPM



SKU: 92560302

Stock: Out of stock contact us for

lead time

Categories: Paco LC & NBS

<u>Pumps</u>

Model Number 030-070/5.83AASG6S2ESBQQEPX2 Part Number 92560302

PRODUCT DESCRIPTION Benefits

• 35 % smaller footprint than frame mount design



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Rapid mechanical seal access without motor removal
 - Lifetime of no alignment
 - Footed volute and motor require no base
 - No grouting
- Integrally cast diffuser vane reduces turbulence and need for suction guides

11.1.8 Shaft seals

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants.

Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F (0 °C) are mainly intended for coolants.



We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

Shaft seal diameter [mm]						28, 38	48	55	60
Shaft seal type		Seal faces	Rubber	Code	Temperature range	Max. pressure [PSI] ([bar])			
	Bellows seal, type B, unbalanced	AQ ₁	EPDM	BAQE	32-248 °F (0-120 °C)	232 (16)	232 (16)	90000000000	232 (16)
		BQ ₁	FKM	BBQV	32-194 °F (0-90 °C)	232 (16)	232 (16)		232 (16)
		Q ₇ Q ₇	EPDM	BQQE	-13 to +248 °F (-25 to +120 °C)	232 (16)	232 (16)	232 (16)	232 (16)
		Q ₇ Q ₇	FKM	BQQV	14 to 194 °F (-10 to +90 °C)	232 (16)	232 (16)	232 (16)	232 (16)

Estimated delivery 3 to 4 weeks. Contact us for actual lead time <u>Specs</u>

Manual

ADDITIONAL INFORMATION

Weight 700 lbs

Dimensions $42 \times 20 \times 22 \text{ in}$

Best Efficiency Point 600 GPM @ 115 FTH



www.pfcestore.com - 763-425-7890 / 800-328-2350