

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS **IMPELLER 30HP 040-070**

1000 GPM @ 85 FTH Best Efficiency Point | Ansi Class 125lbs, 5" x 4" | Lifetime of no shaft alignments | Wetted Material: Cast Iron-Stainless-EPDM | 3/60/230-460V, 3600RPM



SKU: 92556023

Stock: Out of stock contact us for

lead time

Categories: Paco LC & NBS

Pumps

Model Number

040-070/5.75AASG6S2ESBOOEOX2 **Part Number** 92560323

PRODUCT DESCRIPTION **Benefits**

• 35 % smaller footprint than frame mount design



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Rapid mechanical seal access without motor removal
 - Lifetime of no alignment
 - Footed volute and motor require no base
 - No grouting
- Integrally cast diffuser vane reduces turbulence and need for suction guides

11.1.8 Shaft seals

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants.

Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F (0 °C) are mainly intended for coolants.



We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

Shaft seal diamete	r [mm]					28, 38	48	55	60	
Shaft seal type		Seal faces	Seal faces Rubber Code Temperature rang				Max. pressure [PSI] ([bar])			
	Bellows seal, type B, unbalanced	AQ ₁	EPDM	BAQE	32-248 °F (0-120 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		BQ ₁	FKM	BBQV	32-194 °F (0-90 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		Q ₇ Q ₇	EPDM	BQQE	-13 to +248 °F (-25 to +120 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		Q ₇ Q ₇	FKM	BQQV	14 to 194 °F (-10 to +90 °C)	232 (16)	232 (16)	232 (16)	232 (16)	

Estimated delivery 3 to 4 weeks. Contact us for actual lead time Specs

Manual

ADDITIONAL INFORMATION

Weight 750 lbs

Dimensions $46 \times 20 \times 22 \text{ in}$

Best Efficiency Point 1000 GPM @ 85 FTH



www.pfcestore.com - 763-425-7890 / 800-328-2350