

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS IMPELLER 3HP 012-070

75 GPM @ 65 FTH Best Efficiency Point | Ansi Class 125lbs, 2" x 1.25" | Lifetime of no shaft alignments | Wetted Material: Cast Iron-Stainless-EPDM | 3/60/230-460, 3600RPM



SKU: 92557769

Stock: Out of stock contact us for

lead time

Categories: Paco LC & NBS

<u>Pumps</u>

Model Number 012-070/4.29AASG6S2ESBQQEIX2 Part Number 92557769

PRODUCT DESCRIPTION Benefits

• 35 % smaller footprint than frame mount design



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Rapid mechanical seal access without motor removal
 - Lifetime of no alignment
 - Footed volute and motor require no base
 - No grouting
- Integrally cast diffuser vane reduces turbulence and need for suction guides

11.1.8 Shaft seals

(0 °C) are mainly intended for coolants.

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants.

Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F



We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

Shaft seal diamete	r [mm]					28, 38	48	55	60	
Shaft seal type		Seal faces	Seal faces Rubber Code Temperature rang				Max. pressure [PSI] ([bar])			
	Bellows seal, type B, unbalanced	AQ ₁	EPDM	BAQE	32-248 °F (0-120 °C)	232 (16)	232 (16)	90000000000	232 (16)	
		BQ ₁	FKM	BBQV	32-194 °F (0-90 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		Q ₇ Q ₇	EPDM	BQQE	-13 to +248 °F (-25 to +120 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		Q ₇ Q ₇	FKM	BQQV	14 to 194 °F (-10 to +90 °C)	232 (16)	232 (16)	232 (16)	232 (16)	

Estimated delivery 3 to 4 weeks. Contact us for actual lead time <u>Specs</u>

Manual

ADDITIONAL INFORMATION

Weight 245 lbs

Dimensions $40 \times 16 \times 18 \text{ in}$

Best Efficiency Point 75 GPM @ 66 FTH



www.pfcestore.com - 763-425-7890 / 800-328-2350