

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS IMPELLER 40HP 015-090

225 GPM @ 350 FTH Best Efficiency Point | Ansi Class 125lbs, 2.5" x 1.50" | Lifetime of no shaft alignments | Wetted Material: Cast Iron-Stainless-EPDM | 3/60/230-460, 3600RPM



SKU: 92559397 Stock: Out of stock contact us for lead time Categories: Paco LC & NBS Pumps

Model Number 015-090/9.84AASG7SDESDOOERX2 **Part Number** 92559397

PRODUCT DESCRIPTION

Benefits

• 35 % smaller footprint than frame mount design

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B



www.pfcestore.com - 763-425-7890 / 800-328-2350

Rapid mechanical seal access without motor removal

- Lifetime of no alignment
- Footed volute and motor require no base

• No grouting

• Integrally cast diffuser vane reduces turbulence and need for suction guides

11.1.8 Shaft seals

(0 °C) are mainly intended for coolants.

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants. Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F 1

We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

Shaft seal diamete	r [mm]					28, 38	48	55	60	
Shaft seal type		Seal faces	Seal faces Rubber Code Temperature rang				Max. pressure [PSI] ([bar])			
	Bellows seal, type B, unbalanced	AQ ₁	EPDM	BAQE	32-248 °F (0-120 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		BQ ₁	FKM	BBQV	32-194 °F (0-90 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		Q7Q7	EPDM	BQQE	-13 to +248 °F (-25 to +120 °C)	232 (16)	232 (16)	232 (16)	232 (16)	
		Q7Q7	FKM	BQQV	14 to 194 °F (-10 to +90 °C)	232 (16)	232 (16)	232 (16)	232 (16)	

Estimated delivery 3 to 4 weeks. Contact us for actual lead time

<u>Specs</u>

<u>Manual</u>

ADDITIONAL INFORMATION

Weight 900 lbs

Dimensions 48 × 22 × 22 in

Best Efficiency Point 230 GPM @ 350 FTH



www.pfcestore.com - 763-425-7890 / 800-328-2350