

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS NBS CENTRIFUGAL PUMP SPLIT COUPLED, CAST IRON, SS IMPELLER 75HP 030-095

1000 GPM @ 205 FTH Best
Efficiency Point | Ansi Class 125lbs,
4" x 3" | Lifetime of no shaft
alignments | Wetted Material: Cast
Iron-Stainless-EPDM |
3/60/230-460V, 3600RPM



SKU: 92560308

Stock: Out of stock contact us for
lead time

Categories: [Paco LC & NBS
Pumps](#)

Model Number

030-095/7.36AASG6S2ESBQQEUX2

Part Number 92560308

PRODUCT DESCRIPTION

Benefits

- 35 % smaller footprint than frame mount design

www.pfcestore.com - 763-425-7890 / 800-328-2350

- Rapid mechanical seal access without motor removal
- Lifetime of no alignment
- Footed volute and motor require no base
- No grouting
- Integrally cast diffuser vane reduces turbulence and need for suction guides

11.1.8 Shaft seals

The operating range of the seals is described for two main applications: pumping of water or pumping of coolants.
Seals with a temperature range of 32 °F (0 °C) and up are mainly used for pumping water, while seals for temperatures below 32 °F (0 °C) are mainly intended for coolants.

We do not recommend that you operate the pump at maximum temperature and maximum pressure at the same time, as it results in reduced seal life and the occurrence of periodic noise.

Table with 7 columns: Shaft seal diameter [mm], Shaft seal type, Seal faces, Rubber, Code, Temperature range, and Max. pressure [PSI] ([bar]). It lists specifications for Bellows seal, type B, unbalanced across four configurations (AQ1, BQ1, Q7Q7) with EPDM and FKM rubber options.

Estimated delivery 3 to 4 weeks. Contact us for actual lead time

Specs

Manual

ADDITIONAL INFORMATION

Weight 1250 lbs
Dimensions 65 × 34 × 26 in
Best Efficiency Point 1000 GPM @ 205 FTH

www.pfcestore.com - 763-425-7890 / 800-328-2350