

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS - PACO LC CENTRIFUGAL PUMP 10707, 1.5HP

CAST IRON/STAINLESS IMPELLER |  
BUNA MECH SEAL | 1.5HP TEFC  
PRE EFF, 1800RPM,  
3/60/208/230-460 VOLTS | 1 X 1.25  
- IMPELLER 7.10" | CONNECTIONS-  
NPS | BEP 57 GPM @ 50 FTH



---

**SKU:** 98879627

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Paco LC & NBS  
Pumps](#)

**Model Number** 10 10707 130008  
2502P

**Part Number** 98879627

## PRODUCT DESCRIPTION

### LC Close Coupled End Suction Pump

- Close Coupled Design – compact construction and space savings
- Registered Fit – eliminates machine tolerance stacking

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Permanent Rigid Alignment – eliminates need for alignments & prolongs seal and bearing life
- Industry-Standard JM Frame Motor – simplifies motor replacement
- Type LCV Pump – offers vertical mounting for increasing space savings
- No Grouting Requirements – easy installation
- NSF61/50 Certifications (available upon request)
- Francis Vane Impeller Design – increases efficiency and reduces NPSH required
- Trimmed and Balanced Impellers – customization, reduced noise and vibration, & prolonged seal and bearing life

## Applications

- HVAC
- Plumbing
- Pressure Boosting
- Industrial
- Water Utility
- Wastewater
- Agriculture

**Estimated delivery is 3 to 4 weeks**

[SPEC & CURVES](#)

[PARTS GUIDE](#)

## ADDITIONAL INFORMATION

|                              |  |
|------------------------------|--|
| <b>Weight</b>                | 100 lbs                                |
| <b>Dimensions</b>            | 26 × 20 × 20 in                        |
| <b>Connections</b>           | <a href="#"><u>1 X 1.25</u></a>        |
| <b>Best Efficiency Point</b> | <a href="#"><u>57 GPM @ 50 FTH</u></a> |

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

|                        |                       |
|------------------------|-----------------------|
| <b>Hertz</b>           | <u>60</u>             |
| <b>Horse Power</b>     | <u>1.5</u>            |
| <b>Motor Type</b>      | <u>TEFC</u>           |
| <b>Phase</b>           | <u>3</u>              |
| <b>RPM</b>             | <u>1800</u>           |
| <b>Voltage</b>         | <u>230-460</u>        |
| <b>Wetted Material</b> | <u>CAST IRON-BUNA</u> |

CAST IRON/STAINLESS IMPELLER | BUNA MECH SEAL | 1.5HP TEFC PRE EFF,  
1800RPM, 3/60/208/230-460 VOLTS | 1 X 1.25 - IMPELLER 7.10" |  
CONNECTIONS- NPS | BEP 57 GPM @ 50 FTH