


www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS - PACO LC CENTRIFUGAL PUMP 10707, 5HP

CAST IRON/STAINLESS IMPELLER |
BUNA MECH SEAL | 5HP TEFC PRE
EFF, 3600RPM, 3/60/208/230-460
VOLTS | 1 X 1.25 - IMPELLER 5.66"
| CONNECTIONS- NPS | BEP 98 GPM
@ 110 FTH



SKU: 98873472

Stock: Out of stock contact us for
lead time

Categories: [Paco LC & NBS
Pumps](#)

Model Number 10 10707 130008
2681P

Part Number 98873472

PRODUCT DESCRIPTION

LC Close Coupled End Suction Pump

- Close Coupled Design – compact construction and space savings
- Registered Fit – eliminates machine tolerance stacking

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Permanent Rigid Alignment – eliminates need for alignments & prolongs seal and bearing life
- Industry-Standard JM Frame Motor – simplifies motor replacement
- Type LCV Pump – offers vertical mounting for increasing space savings
- No Grouting Requirements – easy installation
- NSF61/50 Certifications (available upon request)
- Francis Vane Impeller Design – increases efficiency and reduces NPSH required
- Trimmed and Balanced Impellers – customization, reduced noise and vibration, & prolonged seal and bearing life

Applications

- HVAC
- Plumbing
- Pressure Boosting
 - Industrial
 - Water Utility
 - Wastewater
 - Agriculture

Estimated delivery is 3 to 4 weeks

[SPEC & CURVES](#)

[PARTS GUIDE](#)

ADDITIONAL INFORMATION

| | |
|------------------------------|---|
| Weight | 100 lbs |
| Dimensions | 26 × 20 × 20 in |
| Connections | <u>1 X 1.25</u> |
| Best Efficiency Point | <u>98 GPM @ 110 FTH</u> |

www.pfcstore.com - 763-425-7890 / 800-328-2350

| | |
|------------------------|-----------------------|
| Hertz | <u>60</u> |
| Horse Power | <u>5</u> |
| Motor Type | <u>TEFC</u> |
| Phase | <u>3</u> |
| RPM | <u>3600</u> |
| Voltage | <u>230-460</u> |
| Wetted Material | <u>CAST IRON-BUNA</u> |

CAST IRON/STAINLESS IMPELLER | BUNA MECH SEAL | 5HP TEFC PRE EFF,
3600RPM, 3/60/208/230-460 VOLTS | 1 X 1.25 - IMPELLER 5.66" |
CONNECTIONS- NPS | BEP 98 GPM @ 110 FTH