

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS - PACO LC CENTRIFUGAL PUMP 12709, 7.5HP

CAST IRON/STAINLESS IMPELLER |  
BUNA MECH SEAL | 7.5HP TEFC  
PRE EFF, 3600RPM,  
3/60/208/230-460 VOLTS | 1.50 X  
1.25 - IMPELLER 5.82" |  
CONNECTIONS- NPS | BEP 125 GPM  
@ 120 FTH



---

**SKU:** 98873476

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Paco LC & NBS  
Pumps](#)

**Model Number** 10 12709 130008  
2741P

**Part Number** 98873476

## PRODUCT DESCRIPTION

### LC Close Coupled End Suction Pump

- Close Coupled Design – compact construction and space savings

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Registered Fit – eliminates machine tolerance stacking
- Permanent Rigid Alignment – eliminates need for alignments & prolongs seal and bearing life
- Industry-Standard JM Frame Motor – simplifies motor replacement
- Type LCV Pump – offers vertical mounting for increasing space savings
- No Grouting Requirements – easy installation
- NSF61/50 Certifications (available upon request)
- Francis Vane Impeller Design – increases efficiency and reduces NPSH required
- Trimmed and Balanced Impellers – customization, reduced noise and vibration, & prolonged seal and bearing life

## Applications

- HVAC
- Plumbing
- Pressure Boosting
  - Industrial
  - Water Utility
  - Wastewater
  - Agriculture

**Estimated delivery is 3 to 4 weeks**

[SPEC & CURVES](#)

[PARTS GUIDE](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	157 lbs
<b>Dimensions</b>	28 × 22 × 22 in
<b>Connections</b>	<a href="#"><u>1.25 X 1.50</u></a>
<b>Best Efficiency Point</b>	<a href="#"><u>125 GPM @ 120 FTH</u></a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

<b>Hertz</b>	<u>60</u>
<b>Horse Power</b>	<u>7.5</u>
<b>Motor Type</b>	<u>TEFC</u>
<b>Phase</b>	<u>3</u>
<b>RPM</b>	<u>3600</u>
<b>Voltage</b>	<u>230-460</u>
<b>Wetted Material</b>	<u>CAST IRON-BUNA</u>

CAST IRON/STAINLESS IMPELLER | BUNA MECH SEAL | 7.5HP TEFC PRE EFF,  
3600RPM, 3/60/208/230-460 VOLTS | 1.50 X 1.25 - IMPELLER 5.82" |  
CONNECTIONS- NPS | BEP 125 GPM @ 120 FTH