

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS - PACO LC CENTRIFUGAL PUMP 15951, 25HP

CAST IRON/STAINLESS IMPELLER | BUNA MECH SEAL | 25HP TEFC PRE EFF, 3600RPM, 3/60/208/230-460 VOLTS | 2 X 1.50 - IMPELLER 9.12" | CONNECTIONS- NPS | BEP 190 GPM @ 260 FTH



SKU: 98873501 Stock: Out of stock contact us for lead time Categories: <u>Paco LC & NBS</u> <u>Pumps</u> Tags: <u>GRUNDFOS/PACO PUMPS</u> Model Number 10 15951 140008 2871P Part Number 98873501

PRODUCT DESCRIPTION

LC Close Coupled End Suction Pump

Close Coupled Design – compact construction and space savings
Registered Fit – eliminates machine tolerance stacking

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

 Permanent Rigid Alignment – eliminates need for alignments & prolongs seal and bearing lifeIndustry-Standard JM Frame Motor – simplifies motor replacement

- Type LCV Pump offers vertical mounting for increasing space savings
 - No Grouting Requirements easy installationNSF61/50 Certifications (available upon request)
- Francis Vane Impeller Design increases efficiency and reduces NPSH required
- Trimmed and Balanced Impellers customization, reduced noise and vibration, & prolonged seal and bearing life

Applications

• HVAC

- Plumbing
- Pressure Boosting
 - Industrial
 - Water Utility
 - Wastewater
 - Agriculture

Estimated delivery is 3 to 4 weeks

SPEC & CURVES

PARTS GUIDE

ADDITIONAL INFORMATION

Weight 466 lbs

Dimensions 38 × 22 × 22 in

Best Efficiency Point 190 GPM @ 260 FTH

Connections

<u>1.5 X 2</u>



Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Hertz	<u>60</u>
Horse Power	<u>25</u>
Motor Type	<u>TEFC</u>
Phase	<u>3</u>
RPM	<u>3600</u>
Voltage	<u>230-460</u>
Wetted Material	<u>CAST IRON-BUNA</u>