

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS - PACO LC CENTRIFUGAL PUMP 20709, 20HP

CAST IRON/STAINLESS IMPELLER |
BUNA MECH SEAL | 20HP TEFC PRE
EFF, 3600RPM, 3/60/208/230-460
VOLTS | 2.5 X 2 - IMPELLER 6.70" |
CONNECTIONS- NPS | BEP 250 GPM
@ 180 FTH



SKU: 98872685

Stock: Out of stock contact us for
lead time

Categories: [Paco LC & NBS
Pumps](#)

Tags: [GRUNDFOS/PACO PUMPS](#)

Model Number 10 20709 140008
2851P

Part Number 98872685

PRODUCT DESCRIPTION

LC Close Coupled End Suction Pump

- Close Coupled Design – compact construction and space savings
- Registered Fit – eliminates machine tolerance stacking

www.pfcstore.com - 763-425-7890 / 800-328-2350

- Permanent Rigid Alignment – eliminates need for alignments & prolongs seal and bearing life
- Industry-Standard JM Frame Motor – simplifies motor replacement
- Type LCV Pump – offers vertical mounting for increasing space savings
- No Grouting Requirements – easy installation
- NSF61/50 Certifications (available upon request)
- Francis Vane Impeller Design – increases efficiency and reduces NPSH required
- Trimmed and Balanced Impellers – customization, reduced noise and vibration, & prolonged seal and bearing life

Applications

- HVAC
- Plumbing
- Pressure Boosting
- Industrial
- Water Utility
- Wastewater
- Agriculture

Estimated delivery is 3 to 4 weeks

[SPEC & CURVES](#)

[PARTS GUIDE](#)

ADDITIONAL INFORMATION

Weight	312 lbs
Dimensions	31 × 14 × 14 in
Best Efficiency Point	<u>250 GPM @ 180 FTH</u>
Connections	<u>2 X 2.5</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350

Hertz	<u>60</u>
Horse Power	<u>20</u>
Motor Type	<u>TEFC</u>
Phase	<u>3</u>
RPM	<u>3600</u>
Voltage	<u>230-460</u>
Wetted Material	<u>CAST IRON-BUNA</u>