

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350



## GRUNDFOS - PACO LC CENTRIFUGAL PUMP 20709, 25HP

CAST IRON/STAINLESS IMPELLER |  
BUNA MECH SEAL | 25 HP TEFC  
PRE EFF, 3600RPM,  
3/60/208/230-460 VOLTS | 2.5 X 2 -  
IMPELLER 6.98" | CONNECTIONS-  
NPS | BEP 350 GPM @ 175 FTH



---

**SKU:** 98872687

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Paco LC & NBS](#)  
[Pumps](#)

**Tags:** [GRUNDFOS/PACO PUMPS](#)

**Model Number** 10 20709 140008  
2871P

**Part Number** 98872687

## PRODUCT DESCRIPTION

### LC Close Coupled End Suction Pump

- Close Coupled Design – compact construction and space savings
- Registered Fit – eliminates machine tolerance stacking

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- Permanent Rigid Alignment – eliminates need for alignments & prolongs seal and bearing life
- Industry-Standard JM Frame Motor – simplifies motor replacement
- Type LCV Pump – offers vertical mounting for increasing space savings
- No Grouting Requirements – easy installation
- NSF61/50 Certifications (available upon request)
- Francis Vane Impeller Design – increases efficiency and reduces NPSH required
- Trimmed and Balanced Impellers – customization, reduced noise and vibration, & prolonged seal and bearing life

### **Applications**

- HVAC
- Plumbing
- Pressure Boosting
- Industrial
- Water Utility
- Wastewater
- Agriculture

**Estimated delivery is 3 to 4 weeks**

[SPEC & CURVES](#)

[PARTS GUIDE](#)

### **ADDITIONAL INFORMATION**

|                              |                                          |
|------------------------------|------------------------------------------|
| <b>Weight</b>                | 441 lbs                                  |
| <b>Dimensions</b>            | 38 × 22 × 22 in                          |
| <b>Best Efficiency Point</b> | <a href="#"><u>350 GPM @ 175 FTH</u></a> |
| <b>Connections</b>           | <a href="#"><u>2.5 X 2</u></a>           |

www.pfcestore.com - 763-425-7890 / 800-328-2350

|                 |                       |
|-----------------|-----------------------|
| Hertz           | <u>60</u>             |
| Horse Power     | <u>20</u>             |
| Motor Type      | <u>TEFC</u>           |
| Phase           | <u>3</u>              |
| RPM             | <u>3600</u>           |
| Voltage         | <u>230-460</u>        |
| Wetted Material | <u>CAST IRON-BUNA</u> |