

www.pfcestore.com - 763-425-7890 / 800-328-2350

## **GRUNDFOS SEG SEWAGE GRINDER PUMP**



Submersible pump connections 2"ANSI | Max Temp 104°F | Cord Length 33' | Cast Iron/NBR | 460 Volts | BEP 100 GPM @ 67 FTH

**SKU:** 98280891 | **Stock:** Out of stock contact us for lead time | **Categories:** <u>Grundfos Sewage Pumps</u> | **Tags:** <u>Grundfos Submersible Pumps</u>

> Model Number SEG.A20.40.2.60H Part Number 98280891



www.pfcestore.com - 763-425-7890 / 800-328-2350



## PRODUCT DESCRIPTION

Non-self-priming, single-stage, centrifugal pump with horizontal discharge port, specifically designed for lift and pumping of wastewater containing discharge from toilets. The pump is equipped with a grinder system that grinds destructible solids into small pieces so that they can be led away through pipes of a relatively small diameter.

The surface of the pump is smooth to prevent dirt and impurities from sticking to the pump. A corrosion resistant stainless steel clamp is securing the motor to the pump housing and allow for ease of service of the pump.

Power Cord 33'

Max Temp 104°F

Estimated delivery 3 to 4 weeks

Product photo could vary from the actual product

**CURVE** 

**Databook** 



www.pfcestore.com - 763-425-7890 / 800-328-2350



This pump is equipped with the unique SmartTrim system that enables you to easily restore the factory-set impeller clearance and maintain peak pumping efficiency. To do this, remove the cutter head and adjust the SmartTrim nut on the impeller. This can be done on site without dismantling the pump and without using special tools.

## **ADDITIONAL INFORMATION**

Weight 180 lbs

**Dimensions**  $27 \times 17 \times 17$  in

**Best Efficiency Point** 100 GPM @ 67 FTH

**Connections** 2" ANSI FLANGE

Hertz <u>60</u>

Horse Power <u>4</u>

Motor Type Continuous Duty



## **Clear Solutions Technology Company**

www.pfcestore.com - 763-425-7890 / 800-328-2350

Phase 3

**RPM** 3500

Solid Size <u>Grinder Pump</u>

Voltage 460

Wetted Material CAST IRON-NBR