



GRUNDFOS SEG SEWAGE GRINDER PUMP EXPLOSION PROOF

Submersible pump connections
2"ANSI | Max Temp 104°F | Cord
Length 33' | Cast Iron/NBR | 460
Volts | Explosion Proof Motor |BEP
78 GPM @ 39 FTH



SKU: 98280880

Stock: Out of stock contact us for
lead time

Categories: [Grundfos Sewage
Pumps](#)

Tags: [Grundfos Submersible
Pumps](#)

Model Number

SEG.A20.30.EX.2.60H

Part Number 98280880

PRODUCT DESCRIPTION

Non-self-priming, single-stage, centrifugal pump with horizontal discharge port, specifically designed for lift and pumping of wastewater containing discharge from toilets. The pump is equipped with a grinder system that grinds destructible solids into small pieces so that they can be led away

www.pfcstore.com - 763-425-7890 / 800-328-2350

through pipes of a relatively small diameter.

The surface of the pump is smooth to prevent dirt and impurities from sticking to the pump. A corrosion resistant stainless steel clamp is securing the motor to the pump housing and allow for ease of service of the pump.

Power Cord 33'

Max Temp 104°F

Estimated delivery 3 to 4 weeks

Product photo could vary from the actual product

[CURVE](#)

[Databook](#)



This pump is equipped with the unique SmartTrim system that enables you to easily restore the factory-set impeller clearance and maintain peak pumping efficiency. To do this, remove the cutter head and adjust the SmartTrim nut on the impeller. This can be done on site without dismantling the pump and without using special tools.

www.pfcstore.com - 763-425-7890 / 800-328-2350

ADDITIONAL INFORMATION

| | |
|------------------------------|------------------------|
| Weight | 180 lbs |
| Dimensions | 27 × 17 × 17 in |
| Best Efficiency Point | <u>78 GPM @ 39 FTH</u> |
| Connections | <u>2" ANSI FLANGE</u> |
| Hertz | <u>60</u> |
| Horse Power | <u>3</u> |
| Motor Type | <u>EXPLOSION PROOF</u> |
| Phase | <u>3</u> |
| RPM | <u>3500</u> |
| Solid Size | <u>Grinder Pump</u> |
| Voltage | <u>460</u> |
| Wetted Material | <u>CAST IRON-NBR</u> |