PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

GRUNDFOS SEG SEWAGE GRINDER PUMP EXPLOSION PROOF

Submersible pump connections 2"ANSI | Max Temp 104°F | Cord Length 33' | Cast Iron/NBR | 460 Volts | Explosion Proof Motor |BEP 100 GPM @ 67 FTH

SKU: 98280892
Stock: Out of stock contact us for lead time
Categories: Grundfos Sewage Pumps
Tags: Grundfos Submersible Pumps
Model Number
SEG.A20.40.EX.2.60H
Part Number 98280892

PRODUCT DESCRIPTION

Non-self-priming, single-stage, centrifugal pump with horizontal discharge port, specifically designed for lift and pumping of wastewater containing discharge from toilets. The pump is equipped with a grinder system that grinds destructible solids into small pieces so that they can be led away

through pipes of a relatively small diameter.

The surface of the pump is smooth to prevent dirt and impurities from sticking to the pump. A corrosion resistant stainless steel clamp is securing the motor to the pump housing and allow for ease of service of the pump.

Power Cord 33'

Max Temp 104°F

Estimated delivery 3 to 4 weeks

Product photo could vary from the actual product

CURVE

Databook

This pump is equipped with the unique SmartTrim system that enables you to easily restore the factory-set impeller clearance and maintain peak pumping efficiency. To do this, remove the cutter head and adjust the SmartTrim nut on the impeller. This can be done on site without dismantling the pump and without using special tools.

ADDITIONAL INFORMATION

Weight	180 lbs
Dimensions	27 × 17 × 17 in
Best Efficiency Point	100 GPM @ 67 FTH
Connections	2" ANSI FLANGE
Hertz	60
Horse Power	4
Motor Type	EXPLOSION PROOF
Phase	3
RPM	3500
Solid Size	Grinder Pump
Voltage	460
Wetted Material	CAST IRON-NBR