

www.pfcstore.com - 763-425-7890 / 800-328-2350

GRUNDFOS SEG SEWAGE GRINDER PUMP EXPLOSION PROOF



Submersible pump connections 1.5"ANSI | Max Temp 104°F | Cord Length 33' | Cast Iron/NBR | 460 Volts | Explosion Proof Motor | BEP 70 GPM @ 43 FTH

SKU: 98280871 | **Stock:** Out of stock contact us for lead time | **Categories:** [Grundfos Sewage Pumps](#) | **Tags:** [Grundfos Submersible Pumps](#)

Model Number SEG.A15.20.EX.2.60H
Part Number 98280871

www.pfcstore.com - 763-425-7890 / 800-328-2350



PRODUCT DESCRIPTION

Non-self-priming, single-stage, centrifugal pump with horizontal discharge port, specifically designed for lift and pumping of wastewater containing discharge from toilets. The pump is equipped with a grinder system that grinds destructible solids into small pieces so that they can be led away through pipes of a relatively small diameter.

The surface of the pump is smooth to prevent dirt and impurities from sticking to the pump. A corrosion resistant stainless steel clamp is securing the motor to the pump housing and allow for ease of service of the pump.

Power Cord 33'

Max Temp 104°F

Estimated delivery 3 to 4 weeks

Product photo could vary from the actual product

[CURVE](#)

[Databook](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350



This pump is equipped with the unique SmartTrim system that enables you to easily restore the factory-set impeller clearance and maintain peak pumping efficiency. To do this, remove the cutter head and adjust the SmartTrim nut on the impeller. This can be done on site without dismantling the pump and without using special tools.

ADDITIONAL INFORMATION

Weight	110lbs
Dimensions	25 × 16 × 16 in
Best Efficiency Point	<u>70 GPM @ 43 FTH</u>
Connections	<u>1.5" ANSI</u>
Hertz	<u>60</u>
Horse Power	<u>2</u>
Motor Type	<u>EXPLOSION PROOF</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350

Phase	<u>3</u>
RPM	<u>3500</u>
Solid Size	<u>Grinder Pump</u>
Voltage	<u>460</u>
Wetted Material	<u>CAST IRON-NBR</u>