

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS SEG SEWAGE GRINDER PUMP

Submersible pump connections
1.5"ANSI | Max Temp 104°F | Cord
Length 33' | Cast Iron/NBR | 460
Volts | BEP 70 GPM @ 43 FTH



SKU: 98280869

Stock: Out of stock contact us for
lead time

Categories: [Grundfos Sewage
Pumps](#)

Tags: [Grundfos Submersible
Pumps](#)

Model Number SEG.A15.20.2.60H

Part Number 98280869

PRODUCT DESCRIPTION

Non-self-priming, single-stage, centrifugal pump with horizontal discharge port, specifically designed for lift and pumping of wastewater containing discharge from toilets. The pump is equipped with a grinder system that grinds destructible solids into small pieces so that they can be led away through pipes of a relatively small diameter.

The surface of the pump is smooth to prevent dirt and impurities from

www.pfcstore.com - 763-425-7890 / 800-328-2350

sticking to the pump. A corrosion resistant stainless steel clamp is securing the motor to the pump housing and allow for ease of service of the pump.

Power Cord 33'

Max Temp 104°F

Estimated delivery 3 to 4 weeks

Product photo could vary from the actual product

[CURVE](#)

[Databook](#)



This pump is equipped with the unique SmartTrim system that enables you to easily restore the factory-set impeller clearance and maintain peak pumping efficiency. To do this, remove the cutter head and adjust the SmartTrim nut on the impeller. This can be done on site without dismantling the pump and without using special tools.

www.pfcestore.com - 763-425-7890 / 800-328-2350

ADDITIONAL INFORMATION

| | |
|-----------------------|------------------------|
| Weight | 110 lbs |
| Dimensions | 25 × 16 × 16 in |
| Best Efficiency Point | <u>70 GPM @ 43 FTH</u> |
| Connections | <u>1.5" ANSI</u> |
| Hertz | <u>60</u> |
| Horse Power | <u>2</u> |
| Motor Type | <u>Continuous Duty</u> |
| Phase | <u>3</u> |
| RPM | <u>3500</u> |
| Solid Size | <u>Grinder Pump</u> |
| Voltage | <u>460</u> |
| Wetted Material | <u>CAST IRON-NBR</u> |