



# GRUNDFOS SUBMERSIBLE PUMP THE UNLIFT KP150

20 GPM @ 12 FTH | 1 Phase 115 Volt | 25ft Cord Less Float | 304SS | Connection 1.25"



**SKU:** 011DC201

Stock: Out of stock contact us for

lead time

Categories: Grundfos Wastewater

Submersible Pumps


Model Number KP 150
Part Number 011DC201

# **GALLERY IMAGES**

#### 4.3 Location

The pump can be used in vertical as well as horizontal position with the outlet port as the highest point of the pump. See fig. 3.

During operation, the inlet strainer must always be completely covered by the pumped liquid.







### PRODUCT DESCRIPTION

Grundfos Unilift pumps vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection. The pump is fitted with a suction strainer, a carrying handle and is supplied with a 9.84 ft mains cable. The impeller is a semi-open impeller for 3/8" free passage suitable for pumping groundwater, surface

water, rain water and similar liquids. The pump has a double shaft seal consisting of two lip seals with grease in-between.

## **Estimated delivery 3 to 4 weeks**

Product photo could vary from the actual product

Curve & Specs

Manual

# ADDITIONAL INFORMATION

Weight 20 lbs

**Dimensions**  $10 \times 10 \times 14$  in

**Best Efficiency Point** 20 GPM @ 12 FTH

Connections 1.25" NPT

Phase  $\underline{1}$ 

Solid Size 3/8"

Voltage 115

Wetted Material <u>304SS-EPDM</u>

