

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS SUBMERSIBLE PUMP THE UNLIFT KP250

30 GPM @ 17 FTH | 1 Phase 115 Volt | 25ft Cord Less Float | 304SS | Connection 1.25"



SKU: 012DC201

Stock: Out of stock contact us for lead time

Categories: [Grundfos Wastewater Submersible Pumps](#)

Model Number KP 250 M 1


Part Number 012DC201

GALLERY IMAGES

4.3 Location

The pump can be used in vertical as well as horizontal position with the outlet port as the highest point of the pump. See fig. 3.

During operation, the inlet strainer must always be completely covered by the pumped liquid.



www.pfcestore.com - 763-425-7890 / 800-328-2350

www.pfcstore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

Grundfos Unilift pumps vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection. The pump is fitted with a suction strainer, a carrying handle and is supplied with a 9.84 ft mains cable. The impeller is a semi-open impeller for 3/8" free passage suitable for pumping groundwater, surface water, rain water and similar liquids. The pump has a double shaft seal consisting of two lip seals with grease in-between.

Estimated delivery 3 to 4 weeks

Product photo could vary from the actual product

[Curve & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	20 lbs
Dimensions	10 × 10 × 14 in
Best Efficiency Point	<u>30 GPM @ 17 FTH</u>
Connections	<u>1.25" NPT</u>
Phase	<u>1</u>
Solid Size	<u>3/8"</u>
Voltage	<u>115</u>
Wetted Material	<u>304SS-EPDM</u>

www.pfcstore.com - 763-425-7890 / 800-328-2350

30 GPM @ 17 FTH | 1 Phase 115 Volt | 25ft Cord Less Float | 304SS | Connection 1.25"