

#### www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS VERTICAL CENTRIFUGAL CRN32-2-1 HQQV, SINGLE PHASE

Best Efficiency Point 140 GPM @ 140 FTH



SKU: 99918027 Stock: Out of stock contact us for lead time Categories: Grundfos CRN Pumps

Model Number CRN 32-2-1 A-G-A-V-HQQV Part Number 99918027

# **PRODUCT DESCRIPTION**

#### **Pumps for specific requirements**

The CRN pumps can be customized to meet customer specific requirements. This is due to the "mix-and-match" approach to customization, where the many pump features and options are to be regarded as modules that can be

PFC eStore

Page: 1

Pumps, Filters & Controls store with B2B



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

### combined to create the ideal pump. Motor options

CRN motors are available in many different configurations to meet the requirements presented by the power supply, the pump environment and/or the pumped liquid itself.

- Power supply systems vary in terms of both frequency and voltage, and required protection methods.
- The environment may be explosive, very hot and/or very humid. Special conditions also apply at high altitudes.
- The pumped liquid can call for a special motor solution. High or low viscosities and/or high or low densities may require non-standard motor sizes. You may also need an explosion-proof variant.
- The installation site of the pump may require alternative positions of pump and motor parts, such as terminal box positions and vent screw positions.

#### Shaft seal options

Extreme liquids sometimes call for extreme measures.

- High temperatures damage seal faces unless precautions are taken.
- Concern for safety can necessitate special measures for aggressive, toxic or flammable liquids.
  - Liquids can be harmful to shaft seals because they crystallize, harden or are extremely abrasive.

### **Pump options**

The CRN pump elements can handle the most demanding liquids and pressures, and be adapted to suit many other requirements.

• Horizontal installation if height is a limitation.

Poor inlet conditions mean that NPSH values must be adjusted to avoid cavitation.

• Very high pressures demand special solutions.

## Specs & Curve

### MANUAL



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

**Databook** 

## **ADDITIONAL INFORMATION**

Weight	292 lbs
Dimensions	45 × 18 × 18 in
Best Efficiency Point	<u>140 GPM @ 140 FTH</u>
Phase	1
Voltage	<u>208-230</u>
Wetted Material	<u>316SS-VITON</u>