

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS VERTICAL CENTRIFUGAL VICTAULIC CONNECTIONS CRN15-12- HQQE, THREE PHASE

Best Efficiency Point 80 GPM @  
690 FTH



---

**SKU:** 99917627

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CRN Pumps](#)

**Model Number** CRN 15-12 A-P-A-  
E-HQQE

**Part Number** 99917627

## PRODUCT DESCRIPTION

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

## **Pumps for specific requirements**

The CRN pumps can be customized to meet customerspecific requirements. This is due to the "mix-and-match" approach to customization, where the many pump features and options are to be regarded as modules that can be combined to create the ideal pump.

### **Motor options**

CRN motors are available in many different configurations to meet the requirements presented by the power supply, the pump environment and/or the pumped liquid itself.

- Power supply systems vary in terms of both frequency and voltage, and required protection methods.
- The environment may be explosive, very hot and/or very humid. Special conditions also apply at high altitudes.
- The pumped liquid can call for a special motor solution. High or low viscosities and/or high or low densities may require non-standard motor sizes. You may also need an explosion-proof variant.
- The installation site of the pump may require alternative positions of pump and motor parts, such as terminal box positions and vent screw positions.

### **Shaft seal options**

Extreme liquids sometimes call for extreme measures.

- High temperatures damage seal faces unless precautions are taken.
- Concern for safety can necessitate special measures for aggressive, toxic or flammable liquids.
- Liquids can be harmful to shaft seals because they crystallize, harden or are extremely abrasive.

### **Pump options**

The CRN pump elements can handle the most demanding liquids and pressures, and be adapted to suit many other requirements.

- Horizontal installation if height is a limitation.

Poor inlet conditions mean that NPSH values must be

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

adjusted to avoid cavitation.

- Very high pressures demand special solutions.
- Special surface treatments or certificates

[Specs & Curve](#)

[Manual](#)

[Databook](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	644 lbs
<b>Dimensions</b>	67 × 18 × 18 in
<b>Best Efficiency Point</b>	<a href="#">80 GPM @ 690 FTH</a>
<b>Phase</b>	<a href="#">3</a>
<b>Voltage</b>	<a href="#">230-460</a>
<b>Wetted Material</b>	<a href="#">316SS-EPDM</a>