

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS VFI FLOW TRANSMITTER 1.3 TO 26 GPM

Wetted Material 316SS-Viton | Connections 1.25" Flanges Stainless Steel | Flow Rate 1.3-26 GPM

## **Applications**

- Water treatment and distribution
  - light chemical industry
    - water management
  - pool and water resorts
    - heating
    - air-conditioning
    - cooling towers
    - condensing units
    - solar collectors.



**SKU:** 97688294

**Stock:** Out of stock contact us for

lead time

**Categories:** Grundfos Flow

<u>Sensors</u>

**Tags: GRUNDFOS FLOW SENSORS** 

Model Number VFI 0.3-6 Part Number 97688294



www.pfcestore.com - 763-425-7890 / 800-328-2350

## PRODUCT DESCRIPTION




Fig. 2 Operating principle

The bluff body is designed to optimise the pulse strength of the pressure variations at the position of the differential pressure detector. The bluff body is an integrated part of the injection moulded flow pipe, or supplied as a composite insert solution. Flow ranges are determined by the pipe diameter and the signal processing parameters. The differential pressure detector key elements are a bulk micromachined silicon chip and a microprocessor-based signal-conditioning circuit, both on the same PCB. The conditioning circuit converts the pressure reading to a signal proportional to the flow

through the pipe. The electronics are protected by an IP44 composite housing. The chip has a square membrane, which deflects due to pressure. Strain gauges are incorporated in a Wheatstone bridge configuration on stress intensive positions on the membrane. The pressure and temperature sensitive area (the membrane region) is coated on both sides by an extremely corrosion and diffusion resistive thin film (Silicoat®). The coating provides direct environmental robustness of the chip. The separation of the media and media-free zones is provided by O-ring sealing.



www.pfcestore.com - 763-425-7890 / 800-328-2350

Estimated delivery is 10 to 12 weeks

Product photo could vary from the actual product

General Info

**General Data** 

## **ADDITIONAL INFORMATION**

Weight 17 lbs

**Dimensions**  $15 \times 12 \times 12$  in

Connections 1.25" Flange

Flow <u>1.3 - 26 GPM</u>

**Wetted Material** 316SS-VITON