

www.pfcstore.com - 763-425-7890 / 800-328-2350



ICON PROCESS IN-LINE MAG METER, CARBON STEEL W/PTFE LINER, ELECTRODES HASTELLOY HC, 3" FLANGE

IP68 | NEMA 4X | Signal Output,
4-20ma, Pulse, RS-485 | Power
Supply 120 volt

3" Flange

Designed for pulsating flow

Accuracy $\pm 0.5\%$ | Repeatability
 $\pm 0.1\%$

No Moving Parts | No Clog Design

Estimated deliver 1 to 2 weeks



SKU: MF1000B-80-A-A-A-A-A-A
Stock: Out of stock contact us for
lead time

Categories: [Icon Process Flow
Meters](#)

Part Number MF1000B-80-A-A-A-

PRODUCT DESCRIPTION

4-20mA | Frequency Pulse | RS-485
Standard PTFE Teflon® Liner
High Accuracy: $\pm 0.5\%$ F.S.
Excellent Chemical Resistance
Full Port Design
IP 68 Protection
Carbon Steel Body
PTFE Teflon® Liner

[Data Sheet](#)

[Manual](#)

ADDITIONAL INFORMATION

| | |
|------------------------|-------------------------------------|
| Weight | 25 lbs |
| Dimensions | 10 × 12 × 8 in |
| Connections | 3" ANSI FLANGE |
| Controller Type | Mag Meter |
| Wetted Material | PTFE - Hastelloy Hc |