

www.pfcstore.com - 763-425-7890 / 800-328-2350



## ICON PROCESS IN-LINE MAG METER, CARBON STEEL W/PTFE LINER, ELECTRODES HASTELLOY HC, 4" FLANGE

IP68 | NEMA 4X | Signal Output,  
4-20ma, Pulse, RS-485 | Power  
Supply 120 volt

4" Flange

Designed for pulsating flow

Accuracy  $\div 0.5\%$  | Repeatability  
 $\div 0.1\%$

No Moving Parts | No Clog Design

Estimated deliver 1 to 2 weeks



**SKU:** MF1000B-100-A-A-A-A-A-A  
**Stock:** Out of stock contact us for  
lead time

**Categories:** [Icon Process Flow  
Meters](#)

**Part Number** MF1000B-100-A-A-

www.pfcstore.com - 763-425-7890 / 800-328-2350

A-A-A-A

## PRODUCT DESCRIPTION

4-20mA | Frequency Pulse | RS-485  
Standard PTFE Teflon® Liner  
High Accuracy:  $\pm 0.5\%$  F.S.  
Excellent Chemical Resistance  
Full Port Design  
IP 68 Protection  
Carbon Steel Body  
PTFE Teflon® Liner

[Data Sheet](#)

[Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	35 lbs
<b>Dimensions</b>	14 × 14 × 10 in
<b>Connections</b>	<a href="#">4" ANSI FLANGE</a>
<b>Controller Type</b>	<a href="#">Mag Meter</a>
<b>Wetted Material</b>	<a href="#">PTFE – Hastelloy Hc</a>