

www.pfcstore.com - 763-425-7890 / 800-328-2350



ICON PROCESS IN-LINE MAG METER, CARBON STEEL W/PTFE LINER, ELECTRODES HASTELLOY HC, 8" FLANGE

IP68 | NEMA 4X| Signal Output,
4-20ma, Pulse, RS-485 | Power
Supply 120 volt

8" Flange

Designed for pulsating flow

Accuracy $\pm 0.5\%$ | Repeatability
 $\pm 0.1\%$

No Moving Parts | No Clog Design

Estimated deliver 1 to 2 weeks



SKU: MF1000B-200-A-A-A-A-A
Stock: Out of stock contact us for
lead time

Categories: [Icon Process Flow
Meters](#)

Part Number MF1000B-200-A-A-

A-A-A-A

PRODUCT DESCRIPTION

4-20mA | Frequency Pulse | RS-485
Standard PTFE Teflon® Liner
High Accuracy: ±0.5% F.S.
Excellent Chemical Resistance
Full Port Design
IP 68 Protection
Carbon Steel Body
PTFE Teflon® Liner

[Data Sheet](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	45 lbs
Dimensions	14 × 14 × 10 in
Connections	8" ANSI FLANGE
Controller Type	Mag Meter
Wetted Material	PTFE - Hastelloy Hc