

www.pfcstore.com - 763-425-7890 / 800-328-2350



## ICON PROCESS IN-LINE MAG METER, CARBON STEEL W/PTFE LINER, ELECTRODES HASTELLOY HC, 8" FLANGE

IP68 | NEMA 4X | Signal Output,  
4-20ma, Pulse, RS-485 | Power  
Supply 120 volt

8" Flange

Designed for pulsating flow

Accuracy  $\div 0.5\%$  | Repeatability  
 $\div 0.1\%$

No Moving Parts | No Clog Design

Estimated deliver 1 to 2 weeks



**SKU:** MF1000B-200-A-A-A-A-A-A  
**Stock:** Out of stock contact us for  
lead time

**Categories:** [Icon Process Flow  
Meters](#)

**Part Number** MF1000B-200-A-A-

www.pfcstore.com - 763-425-7890 / 800-328-2350

A-A-A-A

**PRODUCT DESCRIPTION**

4-20mA | Frequency Pulse | RS-485  
Standard PTFE Teflon® Liner  
High Accuracy: ±0.5% F.S.  
Excellent Chemical Resistance  
Full Port Design  
IP 68 Protection  
Carbon Steel Body  
PTFE Teflon® Liner

[Data Sheet](#)

[Manual](#)

**ADDITIONAL INFORMATION**

|                        |                                            |
|------------------------|--------------------------------------------|
| <b>Weight</b>          | 45 lbs                                     |
| <b>Dimensions</b>      | 14 × 14 × 10 in                            |
| <b>Connections</b>     | <a href="#"><u>8" ANSI FLANGE</u></a>      |
| <b>Controller Type</b> | <a href="#"><u>Mag Meter</u></a>           |
| <b>Wetted Material</b> | <a href="#"><u>PTFE – Hastelloy Hc</u></a> |