

www.pfcstore.com - 763-425-7890 / 800-328-2350



ICON PROCESS TKM PADDLE WHEEL FLOW METER, PVC/VITON, 3/4" NPT CONNECTIONS

Monitors flow rate & Flow Total |
Pulse, 4-20ma | Flow 1.5gpm to
45gpm.

Estimated delivery 1 to 2 weeks



- ✓ Pulse | 4-20mA Outputs
- ✓ Flow | Total
- ✓ Revolutionary ShearPro® Paddle Wheel Design
- ✓ Low Pressure Drop
- ✓ NEMA 4X | IP 66 Protection
- ✓ Password Protected Security
- ✓ True Union Design 1/2" - 2"
- ✓ Flange Connection 3" - 4"



SKU: TKM-20-P-T

Stock: Out of stock contact us for
lead time

Categories: [Icon Process Flow
Meters](#)

PRODUCT DESCRIPTION

Industry's Most Accurate & Reliable Paddle Wheel Flow Meters

The TK Series in-line plastic paddle wheel flow meter has been engineered to provide long-term, accurate flow measurement in tough industrial applications.

The paddle wheel assembly consists of an engineered Tefzel® paddle and micro-polished zirconium ceramic rotor pin and bushings.

High performance Tefzel® and Zirconium materials have been selected

[TK Specs](#)

[TK Manual](#)

ADDITIONAL INFORMATION

Weight	15 lbs
Dimensions	8 × 10 × 6 in
Connections	3/4"FNPT
Controller Type	Paddle Wheel
Wetted Material	PVC-VITON

Monitors flow rate & Flow Total | Pulse, 4-20ma | Flow 1.5gpm to 45gpm.

www.pfcstore.com - 763-425-7890 / 800-328-2350

Estimated delivery 1 to 2 weeks



- ✓ Pulse | 4-20mA Outputs
- ✓ Flow | Total
- ✓ Revolutionary ShearPro® Paddle Wheel Design
- ✓ Low Pressure Drop
- ✓ NEMA 4X | IP 66 Protection
- ✓ Password Protected Security
- ✓ True Union Design ½ - 2"
- ✓ Flange Connection 3" - 4"