

www.pfcstore.com - 763-425-7890 / 800-328-2350



ICON PROCESS TKM PADDLE WHEEL FLOW METER, PVC/VITON, 4" FLANGE CONNECTIONS

Monitors flow rate & Flow Total |
Pulse, 4-20ma | Flow 33gpm to
1149gpm.

Ansi 150lb Flanges

Estimated delivery 1 to 2 weeks



- ✓ Pulse | 4-20mA Outputs
- ✓ Flow | Total
- ✓ Revolutionary ShearPro® Paddle Wheel Design
- ✓ Low Pressure Drop
- ✓ NEMA 4X | IP 66 Protection
- ✓ Password Protected Security
- ✓ True Union Design ½ - 2"
- ✓ Flange Connection 3" - 4"



SKU: TKM-100-P-F

Stock: Out of stock contact us for
lead time

www.pfcstore.com - 763-425-7890 / 800-328-2350

Categories: [Icon Process Flow Meters](#)

Part Number TKM-100-P-F

PRODUCT DESCRIPTION

Industry's Most Accurate & Reliable Paddle Wheel Flow Meters

The TK Series in-line plastic paddle wheel flow meter has been engineered to provide long-term, accurate flow measurement in tough industrial applications.

The paddle wheel assembly consists of an engineered Tefzel® paddle and micro-polished zirconium ceramic rotor pin and bushings.

High performance Tefzel® and Zirconium materials have been selected

[TK Specs](#)

[TK Manual](#)

ADDITIONAL INFORMATION

Weight	15 lbs
Dimensions	8 × 10 × 6 in
Connections	4" ANSI FLANGE
Controller Type	Paddle Wheel
Wetted Material	PVC-VITON

www.pfcstore.com - 763-425-7890 / 800-328-2350

Monitors flow rate & Flow Total | Pulse, 4-20ma | Flow 33gpm to 1149gpm.

Ansi 150lb Flanges

Estimated delivery 1 to 2 weeks



- ✔ Pulse | 4-20mA Outputs
- ✔ Flow | Total
- ✔ Revolutionary ShearPro® Paddle Wheel Design
- ✔ Low Pressure Drop
- ✔ NEMA 4X | IP 66 Protection
- ✔ Password Protected Security
- ✔ True Union Design ½ - 2"
- ✔ Flange Connection 3" - 4"