

www.pfcestore.com - 763-425-7890 / 800-328-2350



IWAKI SANWA MP MAG DRIVE PUMP, 316SS, 1X3/4, MP210

Impeller 3.54", 30 GPM @ 40 FTH | Impeller 3.15" 30 GPM @ 30 FTH | **Motor sold separately**

Wetted Material 316SS, Silicon Carbide, PTFE | Temp -4°F to 248°F



SKU: MP210N-1N?0AN Stock: Out of stock contact us for lead time Categories: <u>Iwaki Sanwa Mag</u> <u>Drive</u>

Part Number MP210N-1N?0AN

PRODUCT DESCRIPTION

Silicon Carbide "-D" Bearings allow for limited dry run operation
Single gasket eliminates multiple leak paths found in competitive designs

- One-piece non-welded machined robust rear casing
 - High strength rare earth magnets
- Straddle-mounted and double bearing design prevents shaft deflection and bearing wear

PFC eStore



www.pfcestore.com - 763-425-7890 / 800-328-2350

NEMA Motor provides endless motor possibilities
 Temp range: -22°F to 302°F

Estimated Delivery 3 to 4 weeks

Specifications

ADDITIONAL INFORMATION

Weight	60 lbs
Dimensions	20 × 18 × 18 in
Best Efficiency Point	30 GPM @ 31 FTH, 30 GPM @ 40 FTH