


www.pfcstore.com - 763-425-7890 / 800-328-2350



IWAKI SANWA MP MAG DRIVE PUMP, 316SS, 1X3/4, MP222

Impeller 6.61", 35 GPM @ 155 FTH
| Impeller 5.51" 30 GPM @ 105 FTH
| **Motor sold separately**

Wetted Material 316SS, Silicon
Carbide, PTFE | Temp -4°F to 248°F



SKU: MP222N-1N?0AN

Stock: Out of stock contact us for
lead time

Categories: [Iwaki Sanwa Mag
Drive](#)

Part Number MP222N-1N?0AN

PRODUCT DESCRIPTION

- Silicon Carbide "-D" Bearings allow for limited dry run operation
- Single gasket eliminates multiple leak paths found in competitive designs
 - One-piece non-welded machined robust rear casing
 - High strength rare earth magnets
- Straddle-mounted and double bearing design prevents shaft deflection and bearing wear

www.pfcstore.com - 763-425-7890 / 800-328-2350

- NEMA Motor provides endless motor possibilities
 - Temp range: -22°F to 302°F

Estimated Delivery 3 to 4 weeks

[Specifications](#)

ADDITIONAL INFORMATION

Weight	60 lbs
Dimensions	20 × 18 × 18 in
Best Efficiency Point	<u>30 GPM @ 100 FTH, 35 GPM @ 155 FTH</u>