



## IWAKI SANWA MP MAG DRIVE PUMP, 316SS, 1X3/4, MP222

Impeller 6.61", 35 GPM @ 155 FTH  
| Impeller 5.51" 30 GPM @ 105 FTH  
| **Motor sold separately**

Wetted Material 316SS, Silicon  
Carbide, PTFE | Temp -4°F to 248°F



---

**SKU:** MP222N-1N?0AN

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Iwaki Sanwa Mag  
Drive](#)

**Part Number** MP222N-1N?0AN

## PRODUCT DESCRIPTION

- Silicon Carbide “-D” Bearings allow for limited dry run operation
- Single gasket eliminates multiple leak paths found in competitive designs
  - One-piece non-welded machined robust rear casing
  - High strength rare earth magnets
- Straddle-mounted and double bearing design prevents shaft deflection and bearing wear

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

- NEMA Motor provides endless motor possibilities
  - Temp range: -22°F to 302°F

**Estimated Delivery 3 to 4 weeks**

[Specifications](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	60 lbs
<b>Dimensions</b>	20 × 18 × 18 in
<b>Best Efficiency Point</b>	<u><a href="#">30 GPM @ 100 FTH, 35 GPM @ 155 FTH</a></u>

Impeller 6.61", 35 GPM @ 155 FTH | Impeller 5.51" 30 GPM @ 105 FTH | **Motor sold separately**

Wetted Material 316SS, Silicon Carbide, PTFE | Temp -4°F to 248°F