

www.pfcestore.com - 763-425-7890 / 800-328-2350



MOYNO® SANITARY PUMP SINGLE STAGE, STAINLESS STEEL WITH EPDM

CONTACT US FOR PRICING | .75

GPM Per 100 RPM, Max 87 PSI Data based on water @ 68F, Cast Iron, Stator EPDM 70 Durometer, Triclamp connections, Single Mech Seal Car/Ceramic, Rotor Chrome Plated, 1 hp 3/60/230-460v Gear Motor wash down 5:1 turn down, Close Coupled Mounted on Stainless Base. Product photo could vary from the actual product



SKU: FB1BSSB3SBA Stock: Out of stock contact us for lead time Categories: <u>Progressing Cavity</u> <u>Pumps</u> Tags: <u>Moyno Pumps</u>

Model Number Sanitary 1000 Part Number FB1BSSB3SBA



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

Moyno® Sanitary Pumps

Low-shear, non-pulsating Sanitary Pumps transfer shear-sensitive materials with a minimum of turbulence or stress.

Features

Mechanical seals standard Standard models meet 3A and BISSC sanitary requirements with no modifications Close-coupled and open throat models

Performance Features

Minimal product degradation in shear-sensitive applications Long service life in abrasive slurries and corrosive fluids Temperatures to 350° F, viscosities to 1,000,000 cps Handle suspended solids to 1.1" diameter Pressures to 225 psi; capacities from .02 to 345 gpm

Typical Applications

Bread dough & bakery products Sauces, juices & jellies Meat & dairy products Wine Yogurt Chemical feed

Estimated delivery is 6 to 10 weeks

Contact us for actual Lead times

Product photo could vary from the actual product

Sanitary Curve

Sanitary Dimensions

Sanitary Service Manual

PFC eStore

August 15, 2025



www.pfcestore.com - 763-425-7890 / 800-328-2350

Our Moyno area covers Minnesota, Wisconsin, South Dakota, North Dakota & the U.P. Michigan

ADDITIONAL INFORMATION

Weight

Dimensions

250 lbs 40 × 22 × 17 in **Recommended RPM** 100 RPM to 400 RPM